

HERCULITE

EXCEL M Series®

Specifications

Description: PVC composite that utilizes a hybrid construction

technology providing both the chemical bond found in typical coated fabrics and the superior mechanical bond

achieved in composite lamination.

Top Coating: Surface coated with the new "M Series" RainKleen® Finish

Fluoropolymer (PVDF). This surface coating over stabilized

PVC offers exceptional surface abrasion and scratch

resistance.

Weight: 18 oz. per square yard

Width: 62 inches / 157.5 centimeters

Transparency: Opaque (some light color shades do offer illumination)

Abrasion Resistance: Excellent

Dimensional Stability: Excellent

Flexibility: Excellent in both hot and cold environments

Flame Resistance: Meets California State Fire Marshall CSFM Reg. Title 19

Mildew Resistance: Excellent

Chemical Resistance: Excellent

Water Repellency: Excellent – Water Proof

Oil Resistance: Excellent

Sewability: Excellent

Heat Sealability: Excellent. Can be sealed by hot air weg welder or radio

frequency bar type.

P.O. BOX 435, EMIGSVILLE, PA 17318 USA (800) 772-0036 (717) 764-1192 FAX (717) 764-5211 www.herculite.com customercare@herculite.com



HERCULITE

EXCEL M Series®

8-Year Limited Warranty

Herculite Excel M Series[®] Awning Fabrics are guaranteed for a period of eight (8) years from date of original installation against rot or excessive deterioration, mildew stains, excessive loss of strength or color change if they occur in normal use and exposure, including sunlight and normal atmospheric chemicals. (Some color change is unavoidable due to ultraviolet rays and chemicals in the atmosphere).

In the unlikely event of failure of fabric during the eight (8) year period from date of original installation, Herculite Products Inc. will guarantee 100% replacement of the fabric to the original owner of the awning for the first five (5) years. Coverage is prorated for the three (3) year remainder of the warranty with a credit of 1/96th being applied toward the purchase of replacement material for each month remaining on the warranty. Herculite's liability will be limited to the replacement of the fabric only and does not cover labor, installation or graphic decorations.

This warranty protects you against damage to the fabric accessories used under normal conditions. It does not cover damage to the fabric from acts of God, vandalism, neglect or improper use. This warranty requires that the user implement proper care and maintenance as defined within Excel M Series, Handling and Maintenance Instructions.

This warranty is in lieu of all warranties expressed or implied, and, Herculite Products Inc. will not be liable for any consequential or incidental damage. Any implied warranties imposed by law are limited in time to the duration of the expressed warranty.

Some states do not allow limitations on how long an implied warranty lasts or the exclusion or limitation of incidental or consequential damage, so, the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights which vary from state to state.



Herculite White XL5088

Herculite® Excel M Series™

is a revolutionary architectural textile composite. Engineered-in-America, it utilizes a unique hybrid construction which delivers exceptional tear and tensile strength blended with flexibility and softness.

Excel M Series

surface is protected with our RainKleen*
Fluoropolymer and comes with our elegant
Pearl-Lustre finish providing incomparable
abrasion and scratch resistance as well as
extraordinary aesthetic appeal.

Excel M Series

is 100% waterproof, flame retardant, heat and RF weldable, and is well suited for commercial and residential structures alike. It is engineered to protect people and furnishings from weather while maintaining an architectural fabric statement of sustainability.

Typical Properties

Weight	18 oz. +/- 10%
Width	62 in.
Tensile Strength (lb./in.)	W 460 / F 345
Tear Strength (lb.)	W 185 / F 180
Scratch Resistance	Excellent
Substrate Yarn	Polyester
Finish	Pearl Lustre
Surface Treatment	RainKleen Fluoropolymer™
Warranty	8 Year
Flame Retardant	CSFM Reg. Title 19 Meets all standard commercial flame resistance requirements

This information is offered for your general guidance and has been obtained by modern test methods. It is true and accurate to the best of our knowledge at the time of printing.

HERCULITE® **EXCEL M Series**

